LotharF MikroKopter.de This page as an **PDF-Document**? Click on that Symbol and wait a little moment... --->

MikroKopter-Tool

• <u>deutsch</u>

• 🔲 <u>français</u>

See also: Link

Inhaltsverzeichnis


- 1. MikroKopter-Tool
 - 1. Download
 - 2. <u>Connecting preparation</u>
 - 3. First start of KopterTool
 - 4. Connection of modules
 - 5. First Connection
- 2. <u>Choosing Assemblies/Settings</u>
 - 1. Assemblies
 - 2. <u>Settings</u>
- 3. <u>Scope</u>
 - 1. <u>Scope Selection</u>
 - 2. <u>Scope Start/Stop</u>
 - 3. <u>Scope Window</u>
- 4. Motortest
- 5. Serial-3D-OSD
 - 1. <u>Serial</u>
 - 2. <u>3D</u>
- 1. Button FlightCtrl
- 2. Button NaviCtrl
- 3. <u>OSD</u>
- 6. Terminal-Window
 - 1. COM-Port
 - 2. Debug
 - 3. <u>Choose language</u>
 - 4. Latest Software download
 - 5. <u>Latest Software update</u>
 - 6. Reset EEPROM initializing

MikroKopter-Tool

The <u>MikroKopter tool</u>, short <u>KopterTool</u> is a Windows-program with the settings on all <u>MikroKopter</u>-components such as <u>FlightCtrl</u>, <u>NaviCtrl</u>, <u>MK3Mag</u>, <u>MK-GPS</u>. Supported Windows versions are 98/2000/XP/Windows7 (eventually need admin rights to be awarded).

Win7: Do not copy the MK-Tool to Program Files !

To use a Windows-program like the <u>KopterTool</u> on a **MAC**, you need on your MAC a program like e.g. Darwine or WineBottler.



Download


The <u>KopterTool</u> will not be installed. It is as .zip-file available and can be used directly after unpacking. The actual version you can get here: <u>Download</u>

Win7: Do not copy the MK-Tool to Program Files !

Connecting preparation

In front of the first start of the <u>KopterTool</u> and to set the individual components, the MK-USB have to be installed on the PC.

Bow you can connected and set up the MK-USB to the PC can be found here: MK-USB



(Alternatively, the <u>SerCon</u> be used for the connection. This, however, requires a **correct** COM port. A COM-USB adapter can **not** be used !!)

• If there is no MK-USB (or Sercon) connected to the PC, you cant open/use the <u>KopterTool</u>! Also if there is no item (<u>FlightCtrl</u>, <u>NaviCtrl</u>, etc.) connect, you can't use the settings.

First start of KopterTool

After the MK-USB is set and connected to the PC the KopterTool can be open.

At the first start you see the license window:

Important		
Bitte bestätigen s	ie die Lizenz- /Nutzungsbedingungen für da	s MikroKopter Projekt.
Please confirm th	e license/terms of use for the MikroKopter p	roject.
Copyright (c) 2007-2009 ł Nur für den privaten Gebr	http://www.MikroKopter.com auch - FOR NON-COMMERCIAL USE ONLY	
(please scroll down to rea	ad the english text)	
Es gilt für das gesamte Pr dass eine Nutzung (auch Sollten direkte oder indire bzgl. der Nutzungsbeding ************************************	ojekt (Hardware, Software, Binärfiles, Sourcecode und Dokume auszugsweise) nur für den privaten und nichtkommerziellen Gel kte kommerzielle Absichten verfolgt werden, ist mit uns (info@m ungen aufzunehmen. des (mit oder ohne Modifikation) weiterverwendet oder veröffer en Nutzungsbedingungen und diese Nutzungsbedingungen incl auszugesweise) oder sonstige Informationen des MikroKopter-F	ntation), prauch zulässig ist. ikrokopter.de) Kontakt ntlicht, . Copyright müssen dann irrojekts
auf anderen Webseiten o	der sonstigen Medien veröffentlicht werden, muss unsere Web:	eite 🔽
Language file:	Automatic (DE)	
Comport:	COM2	
	Akzeptieren / Accept Abbrechen / Abor	t j

This window displays the license agreement to use the tool <u>MikroKopter</u>. Also you can chose the language and the COM-port.

The COM port should be set to the MK-USB.

(Which COM port is assigned to the MK-USB, you can control in the *Windows Device Manager* under *COM and LPT ports.*)

With a "click" on *Akzeptieren / Accept* you accepted the license conditions, the default language setting and the COM port.

Now you see the start window of the KopterTool:

MikroKopter-Tool VX.X	((c) www.mikrokopter.de	
		- Analog4 Analog3 - Analog2 - Analog1 - Analog0
10 20 30 Analog (click to switch) Analog Analog1 Analog2	40 50 60 70 80 90 100 110 120 130	Scope START STOP Switch to (only from NaviCtri)
Analog3 Analog4 Analog5 Analog6 Analog7	?? → → ↓ ↓ Status Interval Scope Motortest	Serial Channels And
Analog8 Analog9 Analog10 Analog11 Analog12 Analog13 Analog14 Analog15	Status Interval Scope Motortest Flight-Ctrl BL-Ctrl BL-Ctrl Mx3Mag K3Mag	Load (csv) Export (csv) http://www.MikroKopter.com Exit MikroKopter.Tool VX.XX (c) www.mikrokopter.de

(View without attached board)

• ⁽¹⁾ If an incorrect COM port is set, it can be set new in the terminal window of the <u>KopterTool</u>. You can access the terminal windows by pressing the button **Firmware update & Terminal** in the <u>KopterTool</u>.

Left down the COM port can be set.

MikroKopter-To	ol ¥X.XX (c) www.miki	rokopter.de			
Connected to ad Terminal 857600					
		<u> </u>			
COM2	Debug	🚯 🔍 🛕 Up	idate Software (ser	rial)	
5.6					

(With a "click" on the button **Debug...** you can go back to the main window.)

Connection of modules

After completion of a new Kopter the <u>FlightCtrl</u> can be connected to the MK-USB. The <u>FlightCtrl</u> and also the other (connected) components (such as <u>NaviCtrl</u>, MK3Mag, etc.) can be programmed now.

Onnection to the Kopter:

- Flight-Ctrl single installed =>
 - ♦ MK-USB is connected to the 10-pin connector "Ext" of the Flight-Ctrl.

Flight-Ctrl and GPS system (NaviCtrl, MK3Mag, MK-GPS) installed =>

♦ MK-USB is connected to the 10-pin connector "Debug" of the <u>NaviCtrl</u>.

The 10-pin ribbon cable must be connected from terminal "1" (red-marked side) to the terminal "1" of each board !

The contact "1" is marked on the boards with a print.

04/19/24 02:50:20

en/MikroKopterTool




Important:

If the ready copter is connected, the jumper should be open at the MK-USB and supplied by a lipo or a regulated power supply.

Especially for first operation it is highly recommended to use the regulated power supply because if errors occur the components will be not destroyed.

Here are some examples of how to connect the modules to the MK-USB.



Are the boards, as shown in the pictures, individually connected, the jumper to supply power to the components should be closed on the MK-USB.


First Connection

Depending on whether the Kopter is connected to the <u>FlightCtrl</u> or when using the GPS system on the <u>NaviCtrl</u>, the startup screen should look like this:

Kopter with <u>FlightCtrl</u>, BL-Ctrl and Receiver.

opter with Fl

04/19/24 02:50:20



Choosing Assemblies/Settings

Assemblies

The different assemblies (<u>FlightCtrl</u>, <u>NaviCtrl</u>, <u>MK3Mag</u>, <u>GPS-Modul</u>) will be selected via the button. The function of the individual modules can be displayed in the Scope and the analog display in the main window of the <u>KopterTool</u>.

Settings 💥							
witch to (only	from NaviCtr						
-> NaviCtrl	-> FlightCr						
-> MKGPS	-> MK3Mac						

A description of each displayed information you will find here: <u>SwitchTo</u>...

Settings

All settings to the Kopter are made on Settings.

If all modules are connected together the settings for all components are made centrally. To turn into the "Settings..." you **must** choose the <u>*FlightCtrl*</u>.

Setting	IS 🔀
witch to (only	rfrom NaviCtrl
-> NaviCtrl	-> FlightCrl
-> MKGPS	-> MK3Mac

A description of the settings and the different tabs you will find here: <u>MK-Parameter</u>...

If you open the "Settings..." first time, you will see the EasySetup. Here you can set the Kopter easy and fast.

A description of the EasySetup and the different tabs you will find here: <u>EasySetup</u>...

INFO

If you select the Settings and see this window...



... then the <u>KopterTool</u> Version is not compatible to the software version on the <u>FlightCtrl</u> and/or <u>NaviCtrl</u>. Then you should update the <u>FlightCtrl</u> / <u>NaviCtrl</u> with the latest software version. (<u>Update</u>) (Alternatively, it could also be used an older version of <u>KopterTool</u>.)

Scope


In the Scope window the functions of the modules are checked. You can determine by selecting the individual functions which scope is displayed.

10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 20			 		 		 		 		

Scope Selection

A klick on **Scope** open the selection window.

Here, the individual functions can selected to be displayed in the scope. Depending on the selected module various functions can be selected.



Also you can select on the analog display the value you need with a "right click" of the mouse on it. This will then change the font color of the selected value.

Here are the first 5 values are selected:

AngleNick	48
AngleRoll	28
AccNick	46
AccRoll	
YawGyro	0
Height Value	8
AccZ	-1
Gas	405
Compass Value	0
Voltage [0.1V]	
Receiver Level	0
Gyro Compass	4
Motor 1	
Motor 2	0
Motor 3	0
Motor 4	0


Scope Start/Stop

The scope on the scope window will be started and stoped by pushing the buttons START and STOP.

Scope Window

On the right side the scope lines are listed. Depending on which module is selected / connected, different values are chosen.

By double-clicking the Scope window it can be increased. Even areas in the scope window can be highlighted by marking with the "mouse".



Example: <u>FlightCtrl</u> display for Nick, Roll, Yaw. To get the scope lines, the <u>FlightCtrl</u> must be inclined in the direction of it's corresponding talk: nick / turn!

Motortest

To test the function of each Motor, you can use the "Motortest". To open this Motortest "click" on "Motortest".

Status	Interval	Scope	Motortest	1
Mot	ortest acti	v		89
	Address	¢		
	1	_		

The procedure:

- Activate *Motortest activ*.
- Under *Address* choose the Motor to test.
- Give slowly gas with the *slider*.
- After the Motortest deactivate *Motortest activ*.

O Attention: For the test engine, the propeller should be removed. If propellers are mounted, the Kopter can lift of.

Serial-3D-OSD



Serial



With the button *SerialChannels* the following window opens up. Here you can use and set up more channels.

- ③ To use these additional serial channels, some conditions are necessary.
 - ◆ The Kopter must be hooked up to the PC/Laptop over an additional connection (Wi232 or Bluetooth)
 - In example: a joystick must be connected to the PC and set up.

- The <u>KopterTool</u> must be open to use the function.

A The serial channels do **not** replace the transmitter! A normal transmitter / receiver must be used anyway.

With the button *SerialChannels* the following window opens up. Here you can use and set up more channels.

To each channel (Ch1: ... Ch12:) functions can be asigned to the joystick. Those you can choose under *Axes*, *Buttons* or *POV*.


So that the functions are transferred to the copter it must have a hook at the bottom **"sending the serial channels are active"** to be set.

To each channel now a FUNCTION / POTI can be assigned. This can be done in the Settings: Channels.

3D

> Serial	Channels
📦 3D	6 OSD

After a click on the **3D Button** the simulation of the Kopter bwill be displayed.



With this function you can display the function of the Gyros visually. The behavior of the 3D-Model is exact the same as the original.

Over the variable regulator underneeth the display you can turn the 3D-Model.

(Info: It is normal if the 3D-display moves very slowly and a little bit jerky into one direction)

Button FlightCtrl

If the button "<u>FlightCtrl</u>" was pushed before the additional balance-display will be shown in the 3D-display.

Balance	-30 -20 -1	1111111111 0 0 10	111 1111 111 20 30	- - × 40 50

With the displayed center of gravity you can control while hovering if the Kopter has the center of gravity right in the middle or on a different spot.

To control and to check that you should connect the Kopter with the PC i.e. over a Bluetooth Module or a Wi232.

Throughout an unfavorable assembly of parts it is possible that the center of gravity is not in the middle. Is that the case the dot is moving into the appropriate direction.

Is the center of gravity is not in the middle but pushed into one direction the engines must work with more power to balance the Kopter .

Particularly interesting: Yaw (upper scale). Here you can see if the Kopter wants to yaw still in one direction. That happen if the motors or the frame are not straight assembled.

In that case the Kopter must regulate continuously the direction to be straight. Even here more power is needed and the desired yaw falls more slowly in one direction.

Button NaviCtrl

If the "<u>NaviCtrl</u>" was pushed before the additional Sticks-display will be shown in the 3D-display.

04/19/24 02:50:20

en/MikroKopterTool

Sticks	EIIX
Select mode: Mode 2	GAS: YAW: NICK: ROLL:

With this display you can check the function and the position of both control-sticks. Here you need to set in the display the used Mode on your transmitter (Mode 1-4).

If you move now the control-sticks you will see the identical movements and peaks in the display.


OSD



With the **OSD-display** multiple functions can be used.

In the upper display, in example, the height of the Kopter, the speed, battery level, distance to the start point, etc. can be displayed.

In the lower field maps can be loaded. The position of the Kopter can be displayed. Also, waypoints can be entered and the Kopter can fly automatically.



For the on-screen display (OSD) a data connection is required for the Kopter. This can be done via Bluetooth or Wi232. For a waypoint-flight the radius is limited to 250mtr!


Informations how to use the OSD for e.g. load a map, waypoint setting, POI setting or many other functions can be found here: <u>KopterTool OSD</u>...

Terminal-Window

The Terminal Window will open through a click on *Firmware update & Terminal*.

🖬 Firmware Update & Terminal...

```
The Terminal Window.
```



COM-Port

Here you can set up the COM-Port for the MK-USB.

Only if this is correct set up you will have a connection between the <u>MikroKopter</u> (or individual components) and the <u>KopterTool</u>.



With the green dot on the left side of the COM port, the COM port can be ended and been restarted. Is the dot green, the COM-PORT is "ON".

Debug

With the *Debug* button you can switch back to the <u>KopterTool</u> Main-Window. Debug

Choose language

In the first time the KopterTool is set up automatically by the detected PC speech.

If you decide to have a different language for the <u>KopterTool</u> you need to click on the button 10 to set it up.

In the next window that opens you can choose the language you need. With *Restart* the <u>KopterTool</u> starts with the new language.



• 🔍 More languages

In the program directory you will find the language files as "language_XX.dat". (XX = country code) This is a simple text file that can be edited with a text editor. Everyone can even modify the files or translate a new language.

The format is quite simple:

```
english text = translated text¶
e.g.¶
Communication timeout! = Délai de communication trop long¶
```

The best thing is for a new language to use an existing language file, renames it and start the compilation. If there is no translation for a word in the file, it automatically displays the text English.

Anyone who wants can send us new language files, and in the next release it will be taken over...

Latest Software download

The latest software for the individual components of the Mikrokopter can be downloaded with the <u>KopterTool</u>.

A click on the loupe opens the necessary window.

An explaination of the download you will find here: Software Download...

Latest Software update

After the actual software is downloaded you can place it into the necessary module (<u>FlightCtrl</u>, <u>NaviCtrl</u>, etc.) You need to click on the button *Update Software (serial)*...

Firmware Update (seriell)...

An information about the Update you can find here: <u>Software Update</u>...

Reset - EEPROM initializing

To reset the modules (<u>FlightCtrl</u>, <u>NaviCtrl</u>, etc.) back to the standard settings, you can do it on a click of the button with the red triangle.

There are two options for this in the KopterTool:

Option 1:

• Each setting has this red triangle. If you "click" on this, only the selected setting and the channel setting reverts to the default settings.

Option 2:

• If you open the terminal window and "click" on this red triangle, you will reset all settings to the default setting. Only the channel settings will stay as the are.



• After a "BIG" Software Updates you should initialize the EEPROM like you see in "Option 2". Since this usually have altered much of the default values you should **not** store old settings. Here, the settings should be set more new.

Of course, then you should calibrate the ACC and the compass once again.

<u>KategorieAnleitung KategorieTools</u>